



MATS FOR PROFESSIONAL USE

Indoor – Contract and Installation Matting

380 Swisslon XT™



Indoor - Heavy traffic

380 Swisslon XT™

Premium quality barrier matting, designed to remove walked-in moisture and finer dirt particles in large indoor entrance areas, including wall-to-wall applications.

Our new classic barrier mat, known for its softer yarns, has been enhanced with a mono-filament to offer additional scraping and provide excellent cleaning and absorbing. The new tri-colour grit pattern provides outstanding dirt-hiding characteristics. Great ability to retain moisture (>5,8 litres per m²) and scrape debris from foot traffic while maintaining its great looking appearance for the longest time. A dense heavyweight vinyl backing ensures longevity.

Recommended use:

- Heavy traffic
- For placement in recessed matwell frames (depth 7 mm) or wall-to-wall installations in larger entrances at hotels, shopping malls, cinemas, public buildings, department stores, banks, restaurants and on stairs

Specifications:

- 100% polyamide 6,0 yarns
- Backing: Black vinyl (DOP free)
- Vinyl borders: 2,5 cm on both sides
- Overall thickness: 9 mm
- Weight: 3.6 kg/m²
- Fire rating: En 13501-1 Cfl-S1
- Special characteristics: Free of DOP, free of DMF, free of ozone depleting substances, free of silicone and free of heavy metals

Recommended accessories:

- 083 Bevelled Nosing 2 mm

Standard sizes:

- 60cm x 90cm
- 90cm x 150cm
- 120cm x 180cm

Full rolls:

- 135cm x 20m
- 200cm x 20m

Custom lengths:

- 135cm x linm
- 200cm x linm

Colours:

- Mocha, Cobalt, Anthracite, Granite, Slate Grey

Cleaning instructions:

- Vacuum/shampooing or use injection/extraction method to clean



PRODUCT TESTING





Anthracite (CH)



Cobalt (BU)



Granite (GT)



Slate Grey (GY)



Mocha (BR)

380 Swisslon XT™

Art. nr.	Dimensions	Weight kg
380S0023BR	60cm x 90cm	2,3
380S0035BR	90cm x 150cm	4,9
380S0046BR	120cm x 180cm	7,9
380R0051BR	135cm x 20m	94,6
380R0078BR	200cm x 20m	145,6
380C0051BR	135cm x linm	4,73
380C0078BR	200cm x linm	7,3

Mocha (BR), Cobalt (BU), Anthracite (CH), Granite (GT), Slate Grey (GY)

380 Swisslon XT™

GENERAL DESCRIPTION

Designation	Dust Control Matting
Type	Indoor – Contract and Installation Matting
Description	Premium absorbent installation matting with monofilament scraper yarn.
Surface	Tri-grit speckled pattern
Category	Dust Control Matting
Recommended use	Indoor Heavy traffic
Colours	Brown, Blue, Charcoal, Granite, Grey
Special remarks	(depth 7 mm)
Edges	Vinyl borders: 2,5 cm on both sides

TECHNICAL SPECIFICATIONS

Material	100% polyamide 6,0 yarns
Backing	Black vinyl (DOP free)
Primary backing	Nonwoven PET/PA
Process	Tufting
Yarn Construction	Cut loop pile - velours
Pile weight	850 g/m ²
Total weight	3.6 kg/m ²
Pile height	7 mm
Overall thickness	9 mm
Number of tufts	85500

TESTS

Absorption capacity	TNO W6034	6
Fire rating	EN 13501	En 13501-1 Cfl-S1
Static charge	ISO 6356	<0,1
Comfort class	EN 1307	LC2
Dimensional stability	ISO 2551	<0,4
Light Fastness	ISO 105 B02	6
Water fastness	ISO 105 B01	4
Rubbing fastness	ISO 105 X12	4
Salt water	ISO 105 E02	4
Shampoo	BS 1006	4
Organic solvents	ISO 105 X05	4
Sustainability	Contributes to a cleaner environment by reducing need of cleaning chemicals	
Surface flammability	ASTM D2859	Pass

DIMENSIONS

Standard sizes	Full rolls	Custom lengths
60cm x 90cm	135cm x 20m	135cm x linm
90cm x 150cm	200cm x 20m	200cm x linm
120cm x 180cm		